

SPECIFICATIONS

CopyPrinter DX6334

General

Printing Process
Printer controller built-in, dual cylinder system

Originals
Sheets/Books

Original Size
Platen Glass: Maximum 300mm x 432mm
ADF: Maximum 297mm x 354mm

Print Paper Size
Maximum: 325mm x 447mm
Minimum: 70mm x 148mm

Print Paper Weights
47 - 210g/m²

Print Area
Maximum: 290mm x 412mm

Print Speed
60 - 135ppm for B4 and below
60 - 120ppm for A3

First Print Speed
12 seconds (A4)

Resolution
Scanning: 600 x 400dpi
Printing: 400 x 400dpi

Paper Capacity
1,000 sheets feed and delivery 80g/m²

Image Position
Vertical: ± 15mm
Horizontal: ± 10mm
Minimum movable unit: 0.25mm

Image Modes
Letter, Letter/Photo, Photo, Tint and Pencil

Reproduction Ratios
Preset enlargement: 115, 122, 141, 200%
Preset Reduction: 50, 61, 71, 82, 87, 93%
Zoom 50 - 200% in 1% steps

Power Consumption
Master Making: 355W
Printing: 270W (at 135ppm)
Energy saver mode: Below 8W

Power Source
220 - 240V, 50/60Hz

Dimension (W x D x H)
1,420mm x 705mm x 1,020mm
ADF: 1,420mm x 705mm x 1,130mm

Weight
Platen cover: Below 103.5kg
ADF: Below 110.5kg

Printer (Optional)

Printer Language
Standard: RPCS™
Option: Adobe® PostScript®3™

Interface
Standard: USB2.0,
Ethernet100BaseTX/10BaseT
Option: IEEE1284 Parallel Port,
IEEE802.11b Wireless LAN

Memory
Standard: 128MB (Resident 64MB +
64MB additional memory)
Maximum: 320MB with optional memory
(128MB or 265MB)

PC Operating Systems
Win 95, 98, Me, NT4.0, 2000, XP, Server
2003
Mac OS8.6 - 9.2.2, OSX (10.1 - 10.3 - 10.4)
Note: Mac OS only works for PS3

Network Protocol
TCP/IP, EtherTalk, NetBEUI, IPX/SPX, Apple
Talk

Added Value Features

Combine and Image Repeat Modes,
Skip Feed, Margin Erase, User Codes, Built
in Job Separator, Confidential Mode, Auto
Magnification, Directional Magnification,
Spot colour printing with optional colour
drum units, Overlay Mode, Programme
Mode, Class/Memory Mode, Makeup
Function, A4 master cut with A3 drum, Auto
density control, Security Mode, (Drum Lock,
Eject Master box Lock), Energy Saver Mode
or Auto shut off mode.

Software

SmartDeviceMonitor™, Web Image Monitor

Company management systems applied during the
manufacturing of all Gestetner products conform to
ISO9001 quality and ISO14001 environmental manage-
ment standards.

In compliance with EU RoHS directive
(RoHS: Restriction of Hazardous Substances).

We reserve the right to make amendments to the
technical specifications and external appearance of
this equipment. Please note that the full range of
options shown in this publication may not always be
available. All brand and product names are recognized
and hereby acknowledged, as registered trademarks
of their respective owners.



RICOH



CopyPrinter DX6334



RICOH Home Page: <http://www.ricoh.co.in>

RICOH INDIA LIMITED

CORPORATE OFFICE: 2nd Floor, Salcon Aurum Building, Plot No. 4,
District Centre Jasola, New Delhi - 110 025
Tel: (011) 49103000, 3100, 3200 Fax: (011) 49103000, 3199 Email: ril.info@ricoh.co.in
REGISTERED OFFICE: 1201,,Bldg no.12,Solitaire Corporate Park, Andheri-Ghatkopar,
Link Road,Andheri - East,
Mumbai-400 093, Tel: (022) 22881953/ 54/ 55 Fax: (022) 22881950
Ahmedabad, Bangalore, Bhopal, Bhubaneswar, Chandigarh, Chennai, Coimbatore,
Delhi, Guwahati, Hyderabad, Jaipur, Kochi, Kolkata, Lucknow, Mumbai, Nagpur, Patna,
Pune, Ranchi, Visakhapatnam.

Gestetner
www.gestetner.com

Gestetner
Total Document
Solutions

ACCESSIBLE DOCUMENT
PRODUCTIVITY